

description



OZONEX adapts its manufacturing according to the basins and the volumes to be treated.

1 FRONT WITH IDENTIFICATION

- 1 power-on led (Green)
- ozone production light (Blue)
- 1 on/off switches
- 1 air flow meter

1 ELECTRONIC CARDS

- 1 EHV card - High Voltage
- Time delay
- 1 fuse / 1 ampere

MOUNTING ACCESSORIES

- 1 stainless steel check valves (316.L)
with Viton seals and glass beads
- 1 ozone tube - diameter 6 x 4 in PTFE

PRIVATE POOLS

OZOSPA

1 METAL BOX

- Width: 140mm - Height: 380mm
- Depth: 120mm
- Weight : 5 Kg

1 ELECTRICAL CONNECTIONS

- 220 Volt / 50 HZ
- Power cable (3G 1.5)

1 CORONA OZONE GENERATOR

- Production (+ -) 2 Grs / hour
- For a flow rate of 1 x 20 m³ water / hour
- Air flow from 0 to 20 liters / hour
- 1 ozone outlets

VARIOUS

- 1 air filters
- 1 solenoid valves (on/off – ozone)

OZONE-BEARING MATERIALS

- PTFE for tubes
- PVDF for solenoid valves and fittings
- VITON for seals
- STAINLESS STEEL 316 L for non-return valve
- 1 power supplies 220V / 50HZ
(110V / 60HZ on demand)
- Power consumption : 60 watts / h